



BL4002 - LED

Weight: 22.5 lbs

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Specifications

Material:
All parts are durable 356 cast aluminum. All mounting hardware shall be stainless steel or zinc plated steel.

Lens:
Choice of clear, frosted or white opal polycarbonate lens.

Mounting:
Standard anchor bolts are 3/8" x 10" x 2". Bolts, nuts and washers shall be hot dipped galvanized steel. Bolt pattern diameter 6".

Drivers:
Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED module.

See page 2 table for LED engine and driver specs, voltage and dimming protocols.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
Consult factory for custom or modified designs.

Catalog Logic



Catalog Number	1	2	3	4	5	6
	BL4002					

1	LENS
CL	(Clear Polycarbonate)
FR	(Frosted Polycarbonate)
WH	(White Opal Polycarbonate)

4	COLOR TEMPERATURE (CCT)
	27K (2700K)
	30K (3000K)
	35K (3500K)
	40K (4000K)

6	FINISHES					
	*Marine Grade Finish has an additional charge					
	Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*
	Aspen Green	10	10M	Copper Clay	53	53M
	Cantaloupe	11	11M	Silver	56	56M
	Lilac	12	12M	Black Verde	61	61M
	Putty	13	13M	Painted Chrome	70	70M
	Raw Unfinished	40	NA	Painted Copper	71	71M
	Black	41	41M	Textured Black	72	72M
	Forest Green	42	42M	Matte Black	73	73M
	Bright Red	43	43M	Textured Architectural Bronze	76	76M
	White	44	44M	Textured White	77	77M
	Bright Blue	45	45M	Textured Silver	78	78M
	Sunny Yellow	46	46M			
	Aqua Green	47	47M			
	Galvanized	49	NA			
	Navy	50	50M			
	Architectural Bronze	51	51M			
	Patina Verde	52	52M			
	Consult Factory for additional paint charges and availability.					

2	LIGHT SOURCE & WATTAGES
M010LDD	(10W Cree Module)
M016LDD	(16W Cree Module)
M024LDD	(24W Cree Module)
M037LDD	(37W Cree Module)

5	ACCESSORIES
HSSC90	(90° House Side Shield, polished)
HSSC180	(180° House Side Shield, polished)
IBOLT	(Eye Bolt)
*EMG-LED5	(5W, LED Emergency Driver)
*EMG-LED7	(7W, LED Emergency Driver)
*EMG-LED10	(10W, LED Emergency Driver)
GFI15	(15 Amp GFCI receptacle outlet)
GFI20	(20 Amp GFCI receptacle outlet)
GFI-WPU	(20 Amp GFCI receptacle w/weather proof)
*For Emergency lumen output data, see Resources section at www.ANPlighting.com .	

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____

LED PERFORMANCE				
MODULE				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
10W	2700K	1250	12W	125
	3000K	1250	12W	125
	3500K	1250	12W	125
	4000K	1250	12W	125
16W	2700K	2000	19W	125
	3000K	2000	19W	125
	3500K	2000	19W	125
	4000K	2000	19W	125
24W	2700K	3000	29W	125
	3000K	3000	29W	125
	3500K	3000	29W	125
	4000K	3000	29W	125
37W	2700K	4000	43W	108
	3000K	4000	43W	108
	3500K	4000	43W	108
	4000K	4000	43W	108

MODULE SPECIFICATION:
• Efficacy 108-125 lumens per watt
• Life: L70 50,000 hours
• Color temp: 2700K, 3000K, 3500K and 4000K
• CRI: >90

MODULE LISTINGS
• Fully compliant with the RoHS Directive
• Certifications: CE/UL

MODULE DRIVER SPECIFICATION:
• Input Voltage: 120-277 Volts; 50/60Hz
• Dimmable down to 1%
• 0-10V, TRIAC and ELV dimming protocols are standard.
• Output Current: Constant Current; 440mA to 940mA (model dependent)
• Driver Efficiency > 80%; Power Factor > 0.9
• Integral Surge Protection in conformance to ANSI C62.41 Category A.

WARRANTY
See www.ANPlighting.com for complete fixture warranty.
LED warranty information
• 5 year limited warranty*
*Limited Warranty: A typical year is defined as 4380 hours of operation

ACCESSORIES



HSSC90/HSSC120



IBOLT



EMG-LED 5, 7 & 10



GFI15 & GFI20



GFI-WPU