

Specifications

**Material:**  
Durable A356 cast aluminum and aluminum sheet metal. Hardware is stainless steel or zinc-plated steel.

**Lens:**  
Multiple choices of lens or no lens.

**Fixture Mounting:**  
Post Mount: Post Cap with set screws. Pendant Mount: Hangs from tenon with Dual Clevis Pins.

**Drivers:**  
Universal Voltage 120-277V is standard. 0-10V dimming is standard. (Refer to Driver Specification section for other specifications.)

**Dark Sky Friendly:**  
To maintain dark sky friendly compatibility: ≤ 3000K & no lens.

**Electrical:**  
A lightning surge protective device is standard (20KA<sup>3</sup> Max/10KA<sup>3</sup> Nominal). Approximately 12" of pull wire extends from luminaire. All luminaires are prewired with 0-10V dimming leads. Post Arms and Wall Mounts are also prewired with line voltage & dimming leads.

**Finish:**  
A polyester powder coat high quality finish. Marine grade finish is available.

**Certifications:**  
UL Listed for outdoor, wet location. LED is IP66.


**Modifications:**  
Consult factory for custom or modified designs.

**Buy American:**  
This product is assembled in the USA and meets the Buy America(n) government procurement requirements under FAR, DFARS, and DOT regulations. [Click here for additional information.](#)

LA664 LED

EPA: 1.90  
Weight: 31 lbs.

Catalog Logic



Catalog Number	1	2	3	4	5	6	7	8
LA664								

1	FIXTURE ORIENTATION
1 (Post)	
3 (Pendant)	

2	LENS
NL (No Lens)	
CL (Clear Acrylic)	
FR (Frosted Acrylic)	
SE (Seeded Acrylic)	

3	LIGHT SOURCE & WATTAGES
<b>TIR Performance Platform</b>	
CPS30W18 (30W TIR Performance Platform)	
CPS39W18 (39W TIR Performance Platform, CA Title 24)	
CPS46W18 (46W TIR Performance Platform)	
CPM78W30 (78W TIR Performance Platform)	
CPM90W36 (90W TIR Performance Platform)	
CPL120W48 (120W TIR Performance Platform)	

4	OPTICS
T2 (Type II)	
T3 (Type III)	
T4 (Type IV)	
T5 (Type V)	

5	CCT (COLOR TEMPERATURE)
27K (2700K)	
30K (3000K)	
35K (3500K)	
40K (4000K)	
*Consult Factory for 5000K	

6	ACCESSORIES
CHC (Clear Glass Chimney)	
CHF (Frosted Glass Chimney)	
HSS90 (90° House Side Shield)	
HSS120 (120° House Side Shield)	
*EMG-LED10 (10W LED Emergency Driver, See Below For Compatibility)	
*EMG-LED20 (20W LED Emergency Driver, See Below For Compatibility)	
*EMG-LED30 (30W LED Emergency Driver, See Below For Compatibility)	
HLMSPC-06 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 15' - 30' Sensor Mounting Height)	
HLMSPC-10 (On/Off Motion Sensor/Photocell, High/Low field-configurable; 8' - 15' Sensor Mounting Height)	
PC (Button Photo Cell)	
TLPC (ANSI C136.41 Twist Lock Photocell, includes receptacle and 120-277V photo cell)	
TL5 (ANSI C136.41 5-Pin Twist Lock Receptacle only)	
TL7 (ANSI C136.41 7-Pin Twist Lock Receptacle only)	
AD (AstroDIM™ - Night-time dimming, consult factory)	
FAID (Field Adjustable Internal Dimmer)	

\*Most Emergency Drivers are remote mount only (consult factory). 10W & 30W Emergency Drivers are not compatible with all LED Light Source and Wattages. For percent lumens in emergency mode, see [Technical Section](#)

7	MOUNTING SOURCE	
<b>Post Mount Options</b>		
S3 (Slips over Ø3" pole or tenon)	PA3111	WM4511
S4 (Slips over Ø4" pole or tenon)	PA3113	WM4513
S5 (Slips over Ø5" pole or tenon)	PA5151	WM5133
TN3 (Mounts to Ø3" pole with Ø2-3/8" x 4" tenon)	PA5153	WM5161
TN4 (Mounts to Ø4" pole with Ø2-3/8" x 4" tenon)	PA5411	WM5163
TN5 (Mounts to Ø5" pole with Ø2-3/8" x 4" tenon)	PA5413	WM5601
OM (Other Mounting, Please Specify)	PA8521	WM5603
<a href="#">All Poles</a> <a href="#">All Post Mounts</a> <a href="#">All Wall Mounts</a>		
<b>Column Mount</b>		
CM Column Mount		
<b>Rigid Stem Mount</b>		<b>Pendant Chain Mount</b>
4ST36 (36" Rigid Stem, 4" OD Canopy) Other lengths available, consult factory.	PEND-CH3 (36" Chain/4 5/8" OD Canopy) Other lengths available, consult factory.	
<b>See last page for popular mounting sizes/styles.</b>		

8	FINISHES					
*Premium and Marine Grade Finish have additional charges						
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	Marine Grade*	
Aspen Green	10	10M	Copper Clay	53	53M	
Cantaloupe	11	11M	Silver	56	56M	
Lilac	12	12M	Black Verde	61	61M	
Putty	13	13M	Painted Chrome	70	70M	
Raw Unfinished	40	NA	Painted Copper	71	71M	
Black	41	41M	Textured Black	72	72M	
Forest Green	42	42M	Matte Black	73	73M	
Bright Red	43	43M	Textured Architectural Bronze	76	76M	
White	44	44M	Textured White	77	77M	
Bright Blue	45	45M	Textured Silver	78	78M	
Sunny Yellow	46	46M	<b>PREMIUM FINISH</b>	<b>Premium Grade*</b>	<b>Marine Grade*</b>	
Aqua Green	47	47M	Textured Desert	80	80M	
Galvanized	49	NA	Graystone	82	82M	
Navy	50	50M	Oil Rubbed Bronze	83	83M	
Architectural Bronze	51	51M	Carbon Graphite	96	96M	
Patina Verde	52	52M				
<b>Consult Factory for additional paint charges and availability.</b>						

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

**PERFORMANCE TABLE - TIR PLATFORM - DELIVERED LUMENS**

LED CATALOG	WATTS	DISTRIBUTION	2700K				3000K				3500K				4000K							
			DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G	DELIVERED LUMENS	lm/W	B	U	G
CPS30W18	30W	TYPE II	3025	101	1	0	1	3262	109	1	0	1	3284	109	1	0	1	3284	109	1	0	1
		TYPE III	2993	100	1	0	1	3229	108	1	0	1	3250	108	1	0	1	3250	108	1	0	1
		TYPE IV	3204	107	1	0	1	3456	115	1	0	1	3478	116	1	0	1	3478	116	1	0	1
		TYPE V	3245	108	2	0	1	3500	117	2	0	1	3524	117	2	0	1	3524	117	2	0	1
CPS39W18	39W	TYPE II	3932	101	1	0	1	4241	109	1	0	1	4269	109	1	0	1	4269	109	1	0	1
		TYPE III	3891	100	1	0	1	4197	108	1	0	1	4225	108	1	0	1	4225	108	1	0	1
		TYPE IV	4165	107	1	0	1	4492	115	1	0	1	4522	116	1	0	1	4522	116	1	0	1
		TYPE V	4219	108	3	0	1	4551	117	3	0	1	4581	117	3	0	1	4581	117	3	0	1
CPS46W18	46W	TYPE II	4638	101	1	0	1	5002	109	1	0	1	5035	109	1	0	1	5035	109	1	0	1
		TYPE III	4590	100	1	0	1	4950	108	1	0	1	4983	108	1	0	1	4983	108	1	0	1
		TYPE IV	4913	107	1	0	1	5299	115	1	0	1	5334	116	1	0	1	5334	116	1	0	1
		TYPE V	4976	108	3	0	1	5367	117	3	0	1	5403	117	3	0	1	5403	117	3	0	1
CPM78W30	78W	TYPE II	7864	101	2	0	2	8482	109	2	0	2	8538	109	2	0	2	8538	109	2	0	2
		TYPE III	7782	100	2	0	2	8394	108	2	0	2	8449	108	2	0	2	8449	108	2	0	2
		TYPE IV	8330	107	2	0	2	8985	115	2	0	2	9044	116	2	0	2	9044	116	2	0	2
		TYPE V	8438	108	3	0	2	9101	117	3	0	2	9161	117	3	0	2	9161	117	3	0	2
CPM90W36	90W	TYPE II	9074	101	2	0	2	9787	109	2	0	2	9852	109	2	0	2	9852	109	2	0	2
		TYPE III	8979	100	2	0	2	9685	108	2	0	2	9749	108	2	0	2	9749	108	2	0	2
		TYPE IV	9612	107	2	0	2	10367	115	2	0	2	10436	116	2	0	2	10436	116	2	0	2
		TYPE V	9735	108	3	0	2	10500	117	3	0	2	10570	117	4	0	2	10570	117	4	0	2
CPL120W48	120W	TYPE II	12099	101	2	0	2	13049	109	2	0	2	13136	109	2	0	2	13136	109	2	0	2
		TYPE III	11973	100	2	0	2	12914	108	2	0	2	12999	108	2	0	2	12999	108	2	0	2
		TYPE IV	12816	107	3	0	3	13823	115	3	0	3	13915	116	3	0	3	13915	116	3	0	3
		TYPE V	12981	108	4	0	2	14000	117	4	0	2	14093	117	4	0	2	14093	117	4	0	2

**TIR PERFORMANCE PLATFORM SPECIFICATION**

- Performance, Ceramic-cooling technology
- Distributions: Type II, III, IV, V
- CCT: 2700K, 3000K, 3500K, 4000K
- Life: L70 >50,000 hours
- Ingress Protection: IP66
- Certification: ETL
- CRI: >80, 3 SDCM

**DRIVER SPECIFICATION**

- Universal Input 120-277V
- 0-10V Dimming to 10%
- Power Factor @ Full Load >95%
- THD @ Full Load <10%
- Constant Current Output 50/60Hz
- Operating Temperature: -40°C Minimum
- Ingress Protection: IP66
- Certifications: UL Recognized, CSA, RoHS

**FINISHES**

- A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion. 5-year warranty for aluminum products. 2-year warranty for steel products.
- Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3,000 hours of continuous salt spray and is available in either a textured or gloss surface. 5-year warranty for aluminum products. 2-year warranty for steel products.

**WARRANTY**

See [www.ANPlighting.com](http://www.ANPlighting.com) for complete fixture warranty.

LED warranty information

- 5 year limited warranty\*
- \*Limited Warranty: A typical year is defined as 4,380 hours of operation.

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

**ACCESSORIES**



CHC & CHF



HSS90 & HSS120



EMG-LED10, 20, 30



HLMSPC-06 & HLMSPC-10



PC



TLPC



TL5 & TL7



FAID

**POPULAR POST MOUNTS**

See Post Arm Section on Website for Specification Sheets and additional post arms. Dimensions are Projection x Height.  
[Click here for all Post Mount styles](#)



PA3111 / 25" x 15 1/4"



PA3113 / 25" x 15 1/4"



PA5151 / 14 1/4" x 19 3/4"



PA5153 / 14 1/4" x 19 3/4"



PA5411 / 17 7/8" x 25 1/8"



PA5413 / 17 7/8" x 25 1/8"



PA6211 / 22 3/4" x 26 1/2"



PA6213 / 22 3/4" x 26 1/2"



PA8031 / 20 1/2" x 20 1/4"



PA8033 / 20 1/2" x 20 1/4"



PA8521 / 18 1/4" x 14 1/2"



PA8523 / 18 1/4" x 14 1/2"

**POPULAR WALL MOUNTS**

See Wall Mount Section on Website for Specification Sheets and additional wall mount arms. Dimensions are Projections x Height.  
[Click here for all Wall Mount styles](#)



WM4511 / 17" x 8"



WM4513 / 17" x 8"



WM5131 / 11" x 16 3/8"



WM5133 / 11" x 16 3/8"



WM5161 / 15 3/4" x 13 3/4"



WM5163 / 15 3/4" x 13 3/4"



WM5601 / 17 7/8" x 14"



WM5603 / 17 7/8" x 14"



WM6111 / 20 3/8" x 24"



WM6113 / 20 3/8" x 24"



WM8581 / 17 1/8" x 17 1/2"



WM8583 / 17 1/8" x 17 1/2"

**COLUMN MOUNT**



CM / 5 3/4" SQ x 3 1/2" H

**RIGID STEM MOUNT**



4ST36

**PENDANT CHAIN MOUNT**



PEND-CH3

Project Name: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

**FINISHES COLORS**

STANDARD																				PREMIUM								
WHITE	TEXTURED WHITE	SILVER	PAINTED CHROME	PAINTED GALVANIZED	PUTTY	TEXTURED SILVER	TEXTURED BLACK	MATTE BLACK	BLACK	BLACK VERDE	PATINA VERDE	FOREST GREEN	AQUA GREEN	ASPEN GREEN	BRIGHT BLUE	NAVY	SUNNY YELLOW	CANTALOUPE	LILAC	BRIGHT RED	PAINTED COPPER	COPPER CLAY	ARCHITECTURAL BRONZE	TEXTURED ARCHITECTURAL BRONZE	TEXTURED DESERT	GRAYSTONE	OIL RUBBED BRONZE	CARBON GRAPHITE