



DIMENSION SPECIFICATIONS	
LED Wattage	Width
29w	8 5/8"
46w	8 5/8"
78w	12 1/4"
117w	13 1/2"

PLATFORM RETROFIT KIT - LED

The ANP HighPro LED Platform is available in 29-watt, 46-watt, 78-watt and 117-watt. Each LED module has a non-yellowing, shatter-resistant lens allowing the platform to be exposed. Suitable for retrofit into all ANP down light, cut-off and dark sky compliant luminaires and most other manufacturers' similar luminaires. No heat sink is required.

Catalog Number

1
2
3
4
5

RP
D

1	LIGHT SOURCE & WATTAGES
029LD4	(29w Platform; 400ma Driver)
046LD4	(46w Platform; 400ma Driver)
078LD4	(78w Platform; 400ma Driver)
117LD4	(117w Platform; 400ma Driver)

4	COLOR TEMPERATURE (CCT)
27K	(2700K)
30K	(3000K)
35K	(3500K)
40K	(4000K)

2	DIMMING
D	(Dimming)
See above specifications for LED engine and driver specs, voltage and dimming protocols.	

5	QUOTE NUMBER
0XXXXXX	ANP Quote Number

3	OPTICS
T2	(Type II)
T3	(Type III)
T5	(Type V)

NOTE: ANP Retrofit Kits are custom designed to fit fixture.

PLATFORM				
LED Wattage	CCT	Typical Luminous Flux	System Wattage	Typical Efficacy
29W	2700K	2670	30w	89
	3000K	2670	30w	89
	3500K	3209	30w	107
	4000K	3465	30w	116
46W	2700K	4004	46w	87
	3000K	4004	46w	87
	3500K	4814	46w	105
	4000K	5197	46w	115
78W	2700K	7041	80w	88
	3000K	7041	80w	88
	3500K	8464	80w	106
	4000K	9138	80w	114
117W	2700K	10561	120w	88
	3000K	10561	120w	88
	3500K	12696	120w	106
	4000K	13707	120w	114

WARRANTY

See www.ANPlighting.com for complete fixture warranty.

LED warranty information

- 7 year limited warranty* on Platform LED engines
- 5 year limited warranty* on Platform Drivers

*Limited Warranty: A typical year is defined as 4380 hours of operation. Failure defined as more than 10% of the total platform LED's not operating.

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Specifications

LED
 Efficacy ranges from 80-115 lumens per watt
 Customized lens precisely directs the light
 Operating temperature of -30C to 55C
 Dimmable down to 10%
 Life: L70 is 60,000 hours
 CCT: 2700K, 3000K, 3500K and 4000K
 CRI: >70
 Parallel circuitry ensures consistent light output in the event of single LED failure

LISTINGS
 Fully compliant with the RoHS Directive
 Certifications: ETL
 Rated IP65 with an optional IP66 rating

DRIVER
 Operates at 400mA
 Built in surge protection
 Constant current output 50/60HZ
 Driver Efficiency > 90% power factor above 99%
 120 – 277 volts
 0-10V dimming protocol is standard

Catalog Logic

RP
046LD4
D
T5
40K
0147588

Retrofit Kit Platform
Light Source & Wattage
Dimming
Optic
CCT
ANP Quote Number