

OSSD42M037LDDW35K

TEST: L012013405

TEST LAB: LIGHT LABORATORY, INC.

ISSUE DATE: 01/24/2020

INPUT: 120.0VAC, 42.84W

TEST PROCEDURE: IESNA:LM-79-08



CHARACTERISTICS

Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	3671
Total Luminaire Efficiency	N.A.
Luminaire Efficacy Rating (LER)	86
Total Luminaire Watts	42.84
Ballast Factor	1.00
CIE Type	Direct
Spacing Criterion (0-180)	0.84
Spacing Criterion (90-270)	0.84
Spacing Criterion (Diagonal)	1.16
Basic Luminous Shape	Circular
Luminous Length (0-180)	3.44 ft (Diameter)
Luminous Weight (90-270)	3.44 ft (Diameter)
Luminous Height	0.00 ft

ZONAL LUMEN SUMMARY

Zone	Lumens	%Lamp	%Fixt
0-20	553.27	N.A.	15.10
0-30	1143.42	N.A.	31.10
0-40	1781.46	N.A.	48.50
0-60	3084.44	N.A.	84.00
0-80	3585.71	N.A.	97.70
0-90	3670.79	N.A.	100.00
10-90	3541.23	N.A.	96.50
20-40	1228.19	N.A.	33.50
20-50	2032.17	N.A.	55.40
40-70	1659.14	N.A.	45.20
60-80	501.28	N.A.	13.70
70-80	145.11	N.A.	4.00
80-90	85.08	N.A.	2.30
90-110	0.00	N.A.	0.00
90-120	0.00	N.A.	0.00
90-130	0.00	N.A.	0.00
90-150	0.00	N.A.	0.00
90-180	0.00	N.A.	0.00
110-180	0.00	N.A.	0.00
0-180	3670.79	N.A.	100.00

Total Luminaire Efficiency = N.A.%

POLAR GRAPH

