

MLO Quick Reference Guide

The Model Lighting Ordinance (MLO) is a guide for environmentally responsible outdoor lighting in North America and is the result of extensive efforts by the International Dark Sky Association (IDA) and the Illuminating Engineering Society of North America (IESNA).

Lighting Zones

LZ0	LZ1	LZ2	LZ3	LZ4
Underdeveloped areas of open space, wilderness park, areas near observatories or areas where protection of a dark environment is critical.	Areas that desire low ambient light levels. Single and two family residential. Rural town centers, commercial areas, business parks with limited night time activity.	Areas with moderate ambient lighting levels. Multifamily residential, hotels, neighborhood business districts, churches, schools, hospitals.	Areas with moderately high lighting levels. Commercial corridors, town centers, mixed use, industrial. Shipping and rail yards. Car dealers, gas stations. High night time activity.	Very high ambient lighting levels. Special cases. Extremely unusual installations. High density entertainment districts and heavy use industrial.

Maximum Allowable Backlight, Uplight and Glare (BUG) Ratings

For bug rating definitions, see BUG Rating Quick Reference Guide on back side.


Backlight	LZ0	LZ1	LZ2	LZ3	LZ4
Greater than 2 mounting heights from property line.	B1	B3	B4	B5	B5
1 to less than 2 mounting heights from property line and ideally oriented.	B1	B2	B3	B4	B4
0.5 to 1 mounting heights from property line and ideally oriented.	B0	B1	B2	B3	B3
Less than 0.5 mounting height to property line and properly oriented.	B0	B0	B0	B1	B2
Uplight	LZ0	LZ1	LZ2	L3Z	LZ4
Allowed uplighting rating	U0	U1	U2	U3	U4
Allowed percentage light emission above 90 degrees for street or area lighting.	0%	0%	0%	0%	0%
Glare	LZ0	LZ1	LZ2	LZ	LZ4
Allowed Glare Rating.	G0	G1	G2	G3	G4
Any luminaire not ideally oriented with 1 to less than 2 mounting heights to any property line of concern.	G0	G0	G1	G1	G2
Any luminaire not ideally oriented with 0.5 to less than 1 mounting heights to any property line of concern.	G0	G0	G0	G1	G1
Any luminaire not ideally oriented with less than 0.5 mounting heights to any property line of concern.	G0	G0	G0	G0	G1

To be considered 'ideally oriented', the luminaire must be mounted with the backlight portion of the light output oriented perpendicular and towards the property line of concern.

For complete information regarding use of this data, go to www.darksky.org/mlo

 [Download PDF at anplighting.com/Quick](http://anplighting.com/Quick)


BUG Rating Quick Reference Guide



Backlight Rating

Maximum Zonal Lumens


	B0	B1	B2	B3	B4	B5
BH	110	500	1000	2500	5000	>5000
BM	220	1000	2500	5000	8500	>8500
BL	110	500	1000	2500	5000	>5000



Uplight Rating

Maximum Zonal Lumens

	U0	U1	U2	U3	U4	U5
UH	0	10	100	500	1000	>1000
UL	0	10	100	500	1000	>1000



Glare Rating

Type I, Type II, Type III, Type IV

Maximum Zonal Lumens


	G0	G1	G2	G3	G4	G5
FVH	10	100	225	500	750	>750
BVH	10	100	225	500	750	>750
FH	660	1800	5000	7500	12000	>12000
BH	110	500	1000	2500	5000	>5000

Type V, V Square

Maximum Zonal Lumens

	G0	G1	G2	G3	G4	G5
FVH	10	100	225	500	750	>750
BVH	10	100	225	500	750	>750
FH	660	1800	5000	7500	12000	>12000
BH	660	1800	5000	7500	12000	>12000

For complete information regarding use of this data, see IES TM-15-11.

 [Download PDF at anplighting.com/Quick](https://anplighting.com/Quick)

The luminaire rating for any one rating is determined by the highest rating in each table.

Example: BH zone is rated B1
 BM zone is rated B2
 BL zone is rated B1
 Luminaire backlight rating is B2