
Specifications CB2901



Project: _ Fixture Type: Quantity: _ Customer:

Specifications

All parts are durable 356 cast aluminum and high strength extruded aluminum.

Shafts are available in 4" and 5" diameter and wall thickness of .125 or 188.

All hardware provided shall be stainless steel or zinc plated steel.

Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel.

Bolt pattern diameter is 7".

Access
Hand access opening and cover are provided in cast base. Hand hole cover is secured by two stainless steel machine screws. (Tamper-proof screws provided upon request). See drawing for position

4" bottom hole provided for conduit access.



Grounding:

All cast bases are provided with an All cast bases are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 1/4-20 stainless steel machine

Pole Height: Maximum pole height is 16 feet.

A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

Modifications:Consult factory for custom or modified designs.

Catalog Logic

CB2901 Cast Base

5S16.188 Shaft

GFI20 -

72 Finish

CB2901 Weight: 81 lbs Anchor Bolts: 4

Catalog Number 2 3 1 **CB2901**

Additional heights and pole diameters may be available. Contact factory for your specific needs.

1 Smooth Shaft Catalog No.	1 Fluted Shaft Catalog No.	Shaft Diameter	Finished Height	Wall Thickness
4S8.125	-	4"	8'	.125
4S9.125	-	4"	9'	.125
4S10.125	-	4"	10'	.125
4S11.125	-	4"	11'	.125
4S12.125	-	4"	12'	.125
4S13.125	-	4"	13'	.125
4S14.125	-	4"	14'	.125
•	-	-	-	-
-	4F8.188	4"	8'	.188
-	4F9.188	4"	9'	.188
-	4F10.188	4"	10'	.188
-	4F11.188	4"	11'	.188
4S12.188	4F12.188	4"	12'	.188
4S13.188	4F13.188	4"	13'	.188
4S14.188	4F14.188	4"	14'	.188
4S15.188	4F15.188	4"	15'	.188
4S16.188	4F16.188	4"	16'	.188
-	-	-	-	-
5S12.125	-	5"	12'	.125
5S13.125	-	5"	13'	.125
5S14.125	-	5"	14'	.125
5S15.125	-	5"	15'	.125
5S16.125	-	5"	16'	.125
-	-	-	-	-
5S12.188	5F12.188	5"	12'	.188
5S13.188	5F13.188	5"	13'	.188
5S14.188	5F14.188	5"	14'	.188
5S15.188	5F15.188	5"	15'	.188
5S16.188	5F16.188	5"	16'	.188

2	ACCESSORIES
GFI15 GFI20	(15 amp GFCI receptacle outlet) (20 amp GFCI receptacle outlet)
GFI-WPU	(20 amp GFCI receptacle with weather proof in-use cover)
BAA	(Cast Banner Arm A for 24" wide banner)
BAB	(Cast Banner Arm B for 30" wide banner)
BAC	(Cast Banner Arm C for 30" wide banner)
LR1	(Cast Ladder Rest 1)
LR3	(Cast Ladder Rest 3)
LR4	(Cast Ladder Rest 4)
LR5	(Cast Ladder Rest 5)
SIGN A	(Cast Sign A; 30" x 9", 8 letters/numbers on one line; requires Banner Arm to hang)
SIGN B	(Cast Sign B; 31" x 7", 12 letters/numbers on one line; requires Banner Arm to hang)
SIGN C line, require	(Cast Sign C; 27" x 11", two rows of 8 letters/numbers on each es Banner Arm to hang)
SIGN D	(Cast Sign D; 11" x 6 1/2", 4 letters/numbers on one line)
SIGN E numbers on	(Cast Sign E; comes with pole clamp, 24 1/2" x 6", 9 letters/
FPH1	(Flag Pole Holder)
TP	(Tamper Proof Screws)



Specifications CB2901

Project:		
Fixture Type:	Quantity: _	
Customer:	·	
	Made in USA	Illuminating ENGINEERING SOCIETY

01 02 14 07 12	Raw Unfinished Black Forest Green Bright Red White Bright Blue	53 56 61 70 71	100 109 106 118 105	Copper Clay Silver Black Verde Painted Chrom
02 14 07 12	Forest Green Bright Red White	61 70	106 118	Black Verde
14 07 12	Bright Red White	70	118	Black Verde Painted Chrom
07 12	White	. •		Painted Chrom
12		71	105	
'	Bright Blue			Painted Coppe
23		72	108	Textured Black
	Sunny Yellow	73	125	Matte Black
20	Aqua Green	76	121	Textured Architectural Bronze
IA	Galvanized	77	127	Textured White
11	Navy	78	124	Textured Silver
		10	130	Aspen Green
04	Patina Verde	11	131	Cantaloupe
33	Lilac	13	132	Putty
	11 03	A Galvanized Navy Architectural Bronze Patina Verde	11 Navy 78 12 Architectural Bronze 10 14 Patina Verde 11	A Galvanized 77 127 11 Navy 78 124 03 Architectural 10 130 04 Patina Verde 11 131