





Weight: 48 lbs Anchor Bolts: 4

Project: _ Fixture Type: Quantity: _ Customer:

Specifications

All parts are durable 356 cast aluminum and high strength extruded aluminum.

Shafts are available in 3" and 4" diameter and wall thickness of .125 or .188.

All hardware provided shall be stainless steel or zinc plated steel.

Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel.

Bolt pattern diameter is 10".

Access
Hand access opening and cover are
provided in cast base. Hand hole cover is
secured by two stainless steel machine
screws. (Tamper-proof screws provided upon request). See drawing for position





Grounding

All cast bases are provided with an All cast bases are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 1/4-20 stainless steel machine

Pole Height

Maximum pole height is 16 feet.

A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

Modifications:Consult factory for custom or modified designs.

CB7102 Cast Base

4S16.188 Shaft

GFI20 -

72 Finish

Catalog Number

CB7102

CB7102

2 3 1

Additional heights and pole diameters may be available. Contact factory for your specific needs.

1 Smooth Shaft Catalog No.	1 Fluted Shaft Catalog No.	Shaft Diameter	Finished Height	Wall Thickness	
3S6.125	3F6.125	3"	6'	.125	
3S7.125	3F7.125	3"	7'	.125	
3S8.125	3F8.125	3"	8'	.125	
3S9.125	3F9.125	3"	9'	.125	
3S10.125	3F10.125	3"	10'	.125	
3S11.125	-	3"	11'	.125	
3S12.125	-	3"	12'	.125	
3S13.125	-	3"	13'	.125	
3S14.125	-	3"	14'	.125	
3S10.188	3F10.188	3"	10'	.188	
3S11.188	3F11.188	3"	11'	.188	
3S12.188	3F12.188	3"	12'	.188	
3S13.188	3F13.188	3"	13'	.188	
3S14.188	3F14.188	3"	14'	.188	
-	3F15.188	3"	15'	.188	
-	3F16.188	3"	16'	.188	
-	-	-	-	-	
4S8.125	-	4"	8'	.125	
4S9.125	-	4"	9'	.125	
4S10.125	-	4"	10'	.125	
4S11.125	-	4"	11'	.125	
4S12.125	-	4"	12'	.125	
4S13.125	-	4"	13'	.125	
4S14.125	-	4"	14'	.125	
-	4F8.188	4"	8'	.188	
-	4F9.188	4"	9'	.188	
-	4F10.188	4"	10'	.188	
-	4F11.188	4"	11'	.188	
4S12.188	4F12.188	4"	12'	.188	
4S13.188	4F13.188	4"	13'	.188	
4S14.188	4F14.188	4"	14'	.188	
4S15.188	4F15.188	4"	15'	.188	
4S16.188	4F16.188	4"	16'	.188	

2	ACCESSORIES
GFI15	(15 amp GFCI receptacle outlet)
GFI20	(20 amp GFCI receptacle outlet)
GFI-WPU	(20 amp GFCI receptacle with weather proof in-use cover)
BAA	(Cast Banner Arm A for 24" wide banner)
BAB	(Cast Banner Arm B for 30" wide banner)
BAC	(Cast Banner Arm C for 30" wide banner)
LR1	(Cast Ladder Rest 1)
LR3	(Cast Ladder Rest 3)
LR4	(Cast Ladder Rest 4)
LR5	(Cast Ladder Rest 5)
SIGN A	(Cast Sign A; 30" x 9", 8 letters/numbers on one line; requires Banner Arm to hang)
SIGN B	(Cast Sign B; 31" x 7", 12 letters/numbers on one line; requires Banner Arm to hang)
SIGN C	(Cast Sign C; 27" x 11", two rows of 8 letters/numbers on each line, requires Banner Arm to hang)
SIGN D	(Cast Sign D; 11" x 6 1/2", 4 letters/numbers on one line)
SIGN E	(Cast Sign E; comes with pole clamp, 24 1/2" x 6", 9 letters/ numbers on one line)
FPH1	(Flag Pole Holder)
ТР	(Tamper Proof Screws)



Specifications CB7102

Project:	
Fixture Type:	Quantity:
Customer:	

3 *Premi	um and Mari		IISHES e Finish have additional ch	narges	
Standard Colors	Standard Grade	Marine Grade*	Standard Colors	Standard Grade	
Aspen Green	10	10M	Architectural Bronze	51	51M
Cantaloupe	11	11M	Patina Verde	52	52M
Lilac	12	12M	Copper Clay	53	53M
Putty	13	13M	Silver	56	56M
Raw Unfinished	40	NA	Black Verde	61	61M
Black	41	41M	Painted Chrome	70	70N
Forest Green	42	42M	Painted Copper	71	71N
Bright Red	43	43M	Textured Black	72	72M
White	44	44M	Matte Black	73	73N
Bright Blue	45	45M	Textured Architectural Bronze	76	76N
Sunny Yellow	46	46M	Textured White	77	77N
Aqua Green	47	47M	Textured Silver	78	78N
Galvanized	49	NA	PREMIUM FINISH	Preminum Grade*	Marine Grade
Navy	50	50M	Carbon Graphite	96	96N