



Quick Ship

Project: _____
 Fixture Type: _____ Quantity: _____
 Customer: _____



Specifications

Material:
 All parts are durable 356 cast aluminum and high strength extruded aluminum.

Shaft is 4" diameter and wall thickness of 0.125. All hardware provided shall be stainless steel or zinc plated steel.

Mounting:
 Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel.

Bolt pattern diameter is 8".

Access
 Hand access opening and cover are provided in cast base. Hand hole cover is secured by two stainless steel machine screws. (Tamper-proof screws provided upon request). See drawing for position of hand hole.

8 3/8" bottom hole provided for conduit access.

Grounding:
 All cast bases are provided with an aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 7/8-20 stainless steel machine screw.

Pole Height
 Maximum pole height is 16 feet.

Finish:
 A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:
 Consult factory for custom or modified designs.

Q-CB0101

Weight: 26 lbs
 Anchor Bolts: 3

Catalog Logic

Q-CB0101 **4S14.125** **76**
 Cast Base Shaft Finish

Catalog Number	1	2
	Q-CB0101	4S14.125
		76

1 Additional heights and pole diameters may be available. Contact factory for your specific needs.

Shaft Diameter	Finished Height	Wall Thickness	Smooth Shaft Catalog No.	Fluted Shaft Catalog No.
4"	10'	.125	CB0101-4S10.125	-
4"	11'	.125	CB0101-4S11.125	-
4"	12'	.125	CB0101-4S12.125	-
4"	13'	.125	CB0101-4S13.125	-
4"	14'	.125	CB0101-4S14.125	-
4"	10'	.188	-	CB0101-4F10.188
4"	11'	.188	-	CB0101-4F11.188
4"	12'	.188	-	CB0101-4F12.188
4"	13'	.188	-	CB0101-4F13.188
4"	14'	.188	CB0101-4S14.188	CB0101-4F14.188
4"	15'	.188	CB0101-4S15.188	CB0101-4F15.188
4"	16'	.188	CB0101-4S16.188	CB0101-4F16.188

2 FINISHES

Standard Grade	Marine Grade	Standard Grade	Marine Grade
40	NA Raw Unfinished	53	100 Copper Clay
41	101 Black	56	109 Silver
42	102 Forest Green	61	106 Black Verde
43	114 Bright Red	70	118 Painted Chrome
44	107 White	71	105 Painted Copper
45	112 Bright Blue	72	108 Textured Black
46	123 Sunny Yellow	73	125 Matte Black
47	120 Aqua Green	76	121 Textured Architectural Bronze
49	NA Galvanized	77	127 Textured White
50	111 Navy	78	124 Textured Silver
51	103 Architectural Bronze	10	130 Aspen Green
52	104 Patina Verde	11	131 Cantaloupe
12	133 Lilac	13	132 Putty

Consult factory for additional paint charges and availability