


Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____



Illuminating
ENGINEERING SOCIETY



Specifications

Material:
RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

Glass:
Choice of clear, frosted or prismatic glass.

Ballasts:
Fluorescent Ballast will be electronic. Fluorescent sockets will be 4 pin to accept quad or triple tube lamps.

Electrical:
4-Pin Base Socket; Multi-tap 120v, 208v, 240v & 277v.

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.


Certifications:
Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

Modifications:
Consult factory for custom or modified luminaires.

D616
CFL

Weight: 1.5 lbs.

Catalog Logic



Catalog Number		1	2	3	4	5	6	7
		D616	32WPL	RTC	E6	100GLFRGUPC		
1	LIGHT SOURCE & WATTAGES							
	Flourescent (CFL)							
	GU24 Socket Option							
	26WPL							
	32WPL							
	42WPL							
	26CFLDIM							
	32CFLDIM							
	42CFLDIM							
	(Compact Fluorescent dimming is 0-10v and ballast must be located within 12" of lamp)							
2	BALLAST HOUSING							
	Fluorescent (CFL)							
	RTC (CFL Ballast Canopy)							
	RTCNC (CFL Ballast Canopy/No Spun Cover)							
	DBH (Dimming CFL Ballast Housing)							
3	MOUNTING SOURCES							
	Arm Mounts (Cast Back Plate (CB) Included)							
	E3 E4 E5 E6 E8 E9							
	E10 E11 E12 E13 E15 E18							
	E19 E25 E26							
	(See Step 2 for Ballast Housing Options)							
	Wall Mounts							
	WM40							
	WM54							
	WM74 (CFL Only)							
	WM75 (HID Only)							
	WM317 (CFL Only)							
	WM84							
	Post Mounts (Postline ballast only; 4" OD pole required)							
	PM10							
	PM20							
	PM30							
	PM40							
	PM50							
	PM319							
	Cord Mounts							
	BLC (6' black cord with 1" x 5 3/8" canopy)							
	WHC (6' white cord with 1" x 5 3/8" canopy)							
	Stem Mounts							
	1/2" (13/16" OD Rigid Stems with STC Flat Canopy)							
	2ST6 2ST12 2ST18 2ST24 2ST36 2ST48							
	2ST60 2ST72 2ST96							
	3/4" (1" OD Rigid Stems with STC Flat Canopy)							
	3ST6 3ST12 3ST18 3ST24 3ST36 3ST48							
	3ST60 3ST72 3ST96							
	(See Step 2 for Ballast Housing Options)							
4	GLASS & GUARD							
	Up to 100w Options							
	100GLCL (Clear Glass)							
	100GLFR (Frosted Glass)							
	100GLPR (Prismatic Glass)							
	100GLCLGUP (Clear Glass & Small Wire Guard)							
	100GLFRGUP (Frosted Glass & Small Wire Guard)							
	100GLPRGUP (Prismatic Glass & Small Wire Guard)							
	100GLCLGUPC (Clear Glass & Cast Guard)							
	100GLFRGUPC (Frosted Glass & Cast Guard)							
	100GLPRGUPC (Prismatic Glass & Cast Guard)							
	100GLGUP (Small Wire Guard with No Glass)							
	100GLGUPC (Cast Guard with No Glass)							
	AC (Stipple Glass Acorn)							
	100GLBG (White Ball Glass)							
	Up to 200w Options							
	200GLCL (Clear Glass)							
	200GLFR (Frosted Glass)							
	200GLPR (Prismatic Glass)							
	200GLCLGUP (Clear Glass & Large Wire Guard)							
	200GLFRGUP (Frosted Glass & Large Wire Guard)							
	200GLPRGUP (Prismatic Glass & Large Wire Guard)							
	200GLCLGUPC (Clear Glass & Large Cast Guard)							
	200GLFRGUPC (Frosted Glass & Large Cast Guard)							
	200GLPRGUPC (Prismatic Glass & Large Cast Guard)							
	200GLGUP (Large Wire Guard with No Glass)							
	200GLGUPC (Large Cast Guard with No Glass)							

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

5 ACCESSORIES	
CBC	(Cast back plate Spun Alum Cover)
EMG-CFL	(CFL Emergency Ballast, remote placement)
GR16	(16" Wire Grill)
PC	(Button Photo Cell) Remote Only
SC	(Scroll for Arms)
SLC	(Sloped Ceiling Mount, 20° Max)
SQ	(Square Back Plate)
SWL	(Swivel)
TBK	(Turnbuckle Kit)

6 VOLTAGES			
120	208	240	277

WARRANTY

See www.anplighting.com for complete fixture warranty.

7 FINISHES					
Standard Grade	Marine Grade		Standard Grade	Marine Grade	
40	NA	Raw Unfinished	53	100	Copper Clay
41	101	Black	56	109	Silver
42	102	Forest Green	61	106	Black Verde
43	114	Bright Red	70	118	Painted Chrome
44	107	White	71	105	Painted Copper
45	112	Bright Blue	72	108	Textured Black
46	123	Sunny Yellow	73	125	Matte Black
47	120	Aqua Green	76	121	Textured Architectural Bronze
49	NA	Galvanized	77	127	Textured White
50	111	Navy	78	124	Textured Silver
51	103	Architectural Bronze	10	130	Aspen Green
52	104	Patina Verde	11	131	Cantaloupe
12	133	Lilac	13	132	Putty
Premium Grade	Marine Grade		Premium Grade	Marine Grade	
81	129	Extreme Chrome	64	116	Candy Apple Red
80	117	Textured Desert Stone	65	122	Cobalt Blue
67	119	Butterscotch	82	128	Graystone
66	115	Caramel	69	113	Gunmetal Gray
68	126	Black Silver	83	134	Oil Rubbed Bronze

Consult factory for additional paint charges and availability

Project: _____

Fixture Type: _____ Quantity: _____

Customer: _____

ARM MOUNTS | Dimensions are Projection x Height | CB included with all arms

 E3 32" x 11 7/8"	 E4 26" x 14"	 E5 37" x 16 1/2"	 E6 26" x 9 1/4"
 E8 29 1/4" x 12 1/2"	 E9 28" x 40 5/8"	 E10 52 1/4" x 18"	 E11 35 1/4" x 17 1/4"
 E12 37 3/8" x 2"	 E13 34" x 34 3/8"	 E15 13 3/8" x 10 1/2"	 E18 27 3/4" x 21 3/8"
 E19 22 3/4" x 95 1/8"	 E25 23" x 5 1/4"	 E26 8 1/8" x 6"	

WALL MOUNTS | Dimensions are Projection x Height











POST MOUNTS | Dimensions are Projection x Height

 WM40 13 7/8" x 14 3/4"	 WM54 23 3/8" x 14 1/4"	 PM10 14 1/2" x 25"	 PM20 30 1/8" x 25"
 WM74 22" x 26 1/2" (CFL Only)	 WM75 25" x 26 1/2" (HID Only)	 PM30 21 5/8" x 28 7/8"	 PM40 43 3/8" x 28 7/8"
 WM84 26 1/2" x 57 1/4"	 WM317 15" x 12" (CFL Only)	 PM50 27" x 38"	 PM319 16 5/8" x 27 1/2"

ACCESSORIES

 CBC	 GR16	 PC	 SC
 SLC	 SQ	 SWL	 TBK

GLASS & GUARDS

Glass Legend: CL = Clear FR = Frosted PR = Prismatic	
Glass Only	
	GLCL GLFR GLPR
	AC (Acorn Glass -- Clear Stipple Only)
	GLBG (Ball Glass -- White Only)
Glass with Cast Guard	
	GLCLGUPC GLFRGUPC GLPRGUPC
Glass with Wire Guard	
	GLCLGUP GLFRGUP GLPRGUP
Guards Only	
	GLGUPC (Cast Guard)
	GLGUP (Wire Guard)
Ballast & Driver Housing	
	RTC
	RTCNC
	DBH