

Specifications ORB16-FR-E6

vat.	3 3/4"
	10 1/2"

Project: _ Quantity: _ Fixture Type: _ Customer: _







Specifications

Material:

RLM shades are constructed of heavy duty spun aluminum. Wall back plate and ballast housing are cast aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match

Glass:

Choice of clear, frosted or prismatic glass.

Electrical:

Medium Base Socket, 100w Maximum.

Certifications: Cord mounts are UL Listed for dry locations. Arm mount, stem mount and wall mount are UL Listed for wet locations.

Finish:

A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

Modifications:


Consult factory for custom or modified luminaires.

ORB16

100w max Incandescent

GLASS





Weight: 2.0 lbs

2

sc


SLC

so

SWL

TBK





(Scroll for Arms)

(Turnbuckle Kit)

(Swivel)

(Square Back Plate)

(Sloped Ceiling Mount, 20° Max)

Cord Mounts

(6' black cord with 1" x 5 3/8" canopy)

4 FINISHES						
Standard Grade	Marine Grade		Standard Grade	Marine Grade	•	
40	NA	Raw Unfinished	53	100	Copper Clay	
41	101	Black	56	109	Silver	
42	102	Forest Green	61	106	Black Verde	
43	114	Bright Red	70	118	Painted Chrome	
44	107	White	71	105	Painted Copper	
45	112	Bright Blue	72	108	Textured Black	
46	123	Sunny Yellow	73	125	Matte Black	
47	120	Aqua Green	76	121	Textured Architectural Bronze	
49	NA	Galvanized	77	127	Textured White	
50	111	Navy	78	124	Textured Silver	
51	103	Architectural Bronze	10	130	Aspen Green	
52	104	Patina Verde	11	131	Cantaloupe	
12	133	Lilac	13	132	Putty	
Premium Grade	Marine Grade		Premium Grade	Marine Grade		
81	129	Extreme Chrome	64	116	Candy Apple Red	
80	117	Textured Desert Stone	65	122	Cobalt Blue	
67	119	Butterscotch	82	128	Graystone	
66	115	Caramel	69	113	Gunmetal Gray	
68	126	Black Silver	83	134	Oil Rubbed Bronze	
Consult factory for additional paint charges and availability						

WARRANTY

See www.anplighting.com for complete fixture warranty.

Specifications ORB16-FR-E6

Project: _____ Quantity: _____ Customer:

			Customer:					
ARM MOUNTS Dimensions are Projection x Height CB included with all arms								
	F							
E3 32" x 11 7/8"	E4 26" x 14"	E5 15 7/8 x 37"	E6 26" x 9 1/4"					
		F	\vdash					
E8 29 1/4" x 12 1/2"	E9 28" x 40 5/8"	E10 52 1/4" x 18"	E11 35 1/4" x 17 1/4"					
E12 37 3/8" x 2"	E13 34" x 34 3/8"	E15 13 3/8" x 10 1/2"	E18 27 3/4" x 21 3/8"					
	<u> </u>		LIG 21 3/4 X21 3/0					
E19 22 3/4" x 95 1/8"	E25 23" x 5 1/4"	E26 8 1/8" x 6"						
WALL MOUNTS Dimen	sions are Projection x Height	POST MOUNTS Dimens	ions are Projection x Height					
WM10 15 3/4" x 13 3/4"	WM35 20 1/2" x 25"	PM10 14 1/2" x 25"	PM20 30 1/8" x 25"					
WM40 13 7/8" x 14 3/4"	WM55 20 5/8" x 14 1/4"	PM30 21 5/8" x 28 7/8"	PM40 43 3/8" x 28 7/8"					
WM75 25" x 26 1/2"	WM318 12" x 12 3/4"	PM50 27" x 38"	PM319 16 5/8" x 27 1/2"					
ACCESSORIES								
СВС	GR16	PC	SC					
		The state of the s						
SLC	so	SWL	твк					

