

Project: \_\_\_\_\_  
 Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Customer: \_\_\_\_\_

**Specifications**

**Material:**  
 RLM shades are constructed of heavy duty spun aluminum. All fasteners are stainless steel. Inside of shade is reflective white finish for all colors except galvanized paint finish. Screw hardware may not match paint.

**Electrical:**  
 Universal voltage 120-277 is standard. 0-10V, TRIAC and ELV dimming to 1% protocols are standard for LED modules.

See page 2 table for LED module and driver specs, voltage and dimming protocols

**Certifications:**  
 UL Listed for wet locations.



**Finish:**  
 A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for maximum paint adhesion.


Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

**Modifications:**  
 Consult factory for custom or modified designs.

**WM1927  
 LED**

Weight: 4.0 lbs

**Catalog Logic**



**1 LIGHT SOURCE & WATTAGES**

|   |
|---|
| <b>M009LDD</b> (9w, 850 lumen, Cree module) |
|---|

**2 DISTRIBUTION**

|   |
|---|
| <b>W</b> (T5 Wide Distribution with Dome LED Lens)    |
| <b>N*</b> (T5 Narrow Distribution with Flat LED Lens) |

**3 COLOR TEMPERATURE (CCT)**

|                    |
|--------------------|
| <b>27K</b> (2700K) |
| <b>30K</b> (3000K) |
| <b>35K</b> (3500K) |
| <b>40K</b> (4000K) |

**4 DRIVER HOUSINGS\***

**Wall Mount Options**

|   |
|---|
| <b>RTCNCW</b> (Driver Housing/No Spun Cover for Wall only (E-arms); 5 7/8" OD x 2 5/8" H) |
|---|

\*Driver Housing finish will match fixture finish.

**5 ACCESSORIES\***

|  |
|--|
| <b>*EMG-LED06</b> (6w, LED Emergency Driver, remote placement, Cree module only, Not applicable for 12w LED) |
| <b>PC</b> (Button Photo Cell) Remote Only  |

\*For Emergency lumen output data; see Technical section at [www.ANPlighting.com](http://www.ANPlighting.com)

\*\*Accessory finish will match fixture finish.

**6 FINISHES**

\*Marine Grade Finish has an additional charge

| Standard Colors               | Standard Grade | Marine Grade* | Premium Colors        | Premium Grade | Marine Grade* |
|-------------------------------|----------------|---------------|-----------------------|---------------|---------------|
| Aspen Green                   | 10             | 10M           | High Gloss Black      | 01            | 01M           |
| Cantaloupe                    | 11             | 11M           | Arctic Silver         | 14            | 14M           |
| Lilac                         | 12             | 12M           | Candy Apple Red       | 64            | 64M           |
| Putty                         | 13             | 13M           | Cobalt Blue           | 65            | 65M           |
| Raw Unfinished                | 40             | NA            | Caramel               | 66            | 66M           |
| Black                         | 41             | 41M           | Butterscotch          | 67            | 67M           |
| Forest Green                  | 42             | 42M           | Black Silver          | 68            | 68M           |
| Bright Red                    | 43             | 43M           | Gunmetal Gray         | 69            | 69M           |
| White                         | 44             | 44M           | Mayan Gold            | 79            | NA            |
| Bright Blue                   | 45             | 45M           | Textured Desert Stone | 80            | 80M           |
| Sunny Yellow                  | 46             | 46M           | Extreme Chrome        | 81            | 81M           |
| Aqua Green                    | 47             | 47M           | Graystone             | 82            | 82M           |
| Galvanized                    | 49             | NA            | Oil Rubbed Bronze     | 83            | 83M           |
| Navy                          | 50             | 50M           | Carbon Graphite       | 96            | 96M           |
| Architectural Bronze          | 51             | 51M           |                       |               |               |
| Patina Verde                  | 52             | 52M           |                       |               |               |
| Copper Clay                   | 53             | 53M           |                       |               |               |
| Silver                        | 56             | 56M           |                       |               |               |
| Black Verde                   | 61             | 61M           |                       |               |               |
| Painted Chrome                | 70             | 70M           |                       |               |               |
| Painted Copper                | 71             | 71M           |                       |               |               |
| Textured Black                | 72             | 72M           |                       |               |               |
| Matte Black                   | 73             | 73M           |                       |               |               |
| Textured Architectural Bronze | 76             | 76M           |                       |               |               |
| Textured White                | 77             | 77M           |                       |               |               |
| Textured Silver               | 78             | 78M           |                       |               |               |

Consult Factory for additional paint charges and availability.

**ACCESSORIES**

**PC Button Photo Cell (Remote Only)**

**EMG-LED**

**DRIVER HOUSING**

**RTCNCW**

**7 VOLTAGE**

|                      |
|----------------------|
| <b>UNV</b> (120-277) |
|----------------------|

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_ Quantity: \_\_\_\_\_

Customer: \_\_\_\_\_

**LED MODULE SPECIFICATIONS**

| LED Wattage | CCT   | Typical Luminous Flux | System Wattage | Typical Efficacy |
|-------------|-------|-----------------------|----------------|------------------|
| 9W          | 2700K | 850                   | 11W            | 97               |
|             | 3000K | 850                   | 11W            | 97               |
|             | 3500K | 850                   | 11W            | 97               |
|             | 4000K | 850                   | 11W            | 97               |

**MODULE SPECIFICATION:**

- Efficacy 65-125 lumens per watt
- Life: L70 50,000 hours
- Color temp: 2700K, 3000K, 3500K and 4000K
- CRI: >90

**MODULE LISTINGS**

- Fully compliant with the RoHS Directive
- Certifications: CE/UL

**WARRANTY**See [www.ANPlighting.com](http://www.ANPlighting.com) for complete fixture warranty.

LED warranty information

- 5 year limited warranty\*

\*Limited Warranty: A typical year is defined as 4380 hours of operation

**MODULE DRIVER SPECIFICATION:**

- Input Voltage: 120-277 Volts; 50/60Hz
- Dimmable down to 1%
- 0-10V, TRIAC and ELV dimming protocols are standard.
- Output Current: Constant Current; 440mA to 940mA (model dependent)
- Driver Efficiency > 80%; Power Factor > 0.9
- Integral Surge Protection in conformance to ANSI C62.41 Category A.