Specifications OSPBF12

21"
12 1/5"
<u>* * </u>

Weight: 7.0 lbs

Specifications

Material:
Dome top is constructed of heavy duty spun aluminum.
Shade is of a hard back fabric.
Driver housing is constructed of heavy duty spun aluminum.
All fasteners are stainless steel. Screw hardware may not match paint.

Electrical:
Medium Base Socket, 200w Maximum or GU24 Socket.
Approximately 12" of pull wire extends from fixure. Additional pull wire provided for post mount arms and wall mounts.

Certifications: UL Listed for dry locations.

Catalog Logic

Project: _ Fixture Type: _

Customer: _

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and

Quantity: _

Illuminating

pretreatment process for maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss surface.

Modifications:Consult factory for custom or modified designs.

OSPBF12 200w Max

Medium Base Catalog Number

1

2

10"

3

4

RLM Style

FINISHES

Fabric

OSPBF12 GY - MB - BLC - 72 Lamp

OSPBF12

* Stem finish will match fixture finish.

1	FABRIC SHADE			
BG	(Beige Hard Back Fabric)			
вк	(Black Hard Back Fabric)			
GY	(Gray Hard Back Fabric)			
cus	CUST (Custom Hard Back Fabric)			

2	LAMP BASE	
МВ	(Medium Base, 200w Max)	
GH24	(GU24 Base)	

3 MOUNTING	SOURCES		
	founts** 5 3/8" canopy)		
SSC-BLC (Stainless steel c	able with 6' Black SJT Cord)		
SSC-WHC (Stainless steel c	able with 6' White SJT Cord)		
SSC-XXXX (Stainless steel cable with 6' Color cord. Replace XXXX with color cord designation below)			
**Cord/Cable Canopy finish	will match fixture finish.		
SJT	Cord		
BLC (6' Black SJT Cord)	WHC (6' White SJT Cord)		
Solid Fabric	Colored Cords		
BLSF (6' Black)	ORSF (6' Orange)		
GYSF (6' Gray)	LGSF (6' Lime Green)		
CHSF (6' Chocolate Brown)	KGSF (6' Kelly Green)		
WHSF (6' White)	CBSF (6' Cobalt Blue)		
CASF (6' Cardinal)	SBSF (6' Sky Blue)		
Patterned Fabri	c Colored Cords		
BWHPF (6' Black/White Houndstooth)	BIHPF (6' Brown/Ivory Houndstooth)		
GYCPF (6' Gray/Citrus Yellow)	MOSPF (6' Magenta/Orange Stripe)		
NMTPF (6' Navy Mini Tweed)			
Glossy Fabric	Colored Cords		
GMGF (6' Gun Metal)	SSGF (6' Sterling Silver)		
CPGF (6' Copper Penny)	BRGF (6' Bronze)		

3	M	OUNTI	NG SOL	JRCES ((Continued)*
Stem Mounts*					
1/4"	(1/2	" OD Ster	ns with 45°	Swivel Fl	at Canopy)
IST	S6	1STS12	1STS18	1STS24	1STS36
IST	S48	1STS60	1STS72	1STS96	
1/4" (1/2" OD Rigid Stems with Flat Canopy)					
IST	R6	1STR12	1STR18	1STR24	1STR36
IST	R48	1STR60	1STR72	1STR96	

Standard Colors	Standard Grade	Premium Colors	Premium Grade
Aspen Green	10	High Gloss Black	01
Cantaloupe	11	Arctic Silver	14
Lilac	12	Candy Apple Red	64
Putty	13	Cobalt Blue	65
Raw Unfinished	40	Caramel	66
Black	41	Butterscotch	67
Forest Green	42	Black Silver	68
Bright Red	43	Gunmetal Gray	69
White	44	Mayan Gold	79
Bright Blue	45	Textured Desert Stone	80
Sunny Yellow	46	Extreme Chrome	81
Aqua Green	47	Graystone	82
Galvanized	49	Oil Rubbed Bronze	83
Navy	50	Carbon Graphite	96
Architectural Bronze	51		
Patina Verde	52		
Copper Clay	53		
Silver	56		
Black Verde	61		
Painted Chrome	70		
Painted Copper	71		
Textured Black	72		
Matte Black	73		
Textured Architectural Bronze	76		
Textured White	77		
Textured Silver	78		

WARRANTY

See www.ANPlighting.com for complete fixture warranty

Project: _____ Quantity: _____ Customer: _____

All fabric Color Cords are three conductor, 1/4" diameter





