

Project: _ Fixture Type: ___ Quantity: _ Customer:

Specifications

All parts are durable 356 cast aluminum and high strength extruded

Shafts are available in 3" and 4" diameter and wall thickness of .125 or 188.

All hardware provided shall be stainless steel or zinc plated steel.

Standard anchor bolts provided are 3/4" x 18" x 3". Bolts, nuts and washers shall be hot dipped galvanized steel .

Bolt pattern diameter is 9".

Access
Hand access opening and cover are
provided in cast base. Hand hole cover is
secured by two stainless steel machine
screws. (Tamper-proof screws provided upon request). See drawing for position of hand hole.

5" bottom hole provided for conduit access.





Grounding

All cast bases are provided with an All cast bases are provided with all aluminum grounding lug integrated to inner wall of shaft, 180 degrees to hand hole. Grounding lug is drilled and tapped to accommodate 1/4-20 stainless steel machine

Pole Height Maximum pole height is 16 feet.

Finish:

Finish:
A polyester powder coat high quality finish is electro-statically applied and baked at 430° for exceptional durability and color retention. Products undergo an intensive five-step cleansing and pretreatment process for provincing point of the color. maximum paint adhesion.

Marine grade finish provides superior salt, humidity and UV protection. This coating withstands up to 3000 hours of continuous salt spray, comes with a 5-year warranty and is available in either a textured or gloss

Modifications:Consult factory for custom or modified designs.

Catalog Logic

CB0103 -Cast Base

4S16.188 Shaft

GFI20 -

72 Finish

CB0103

Weight: 35.5 lbs Anchor Bolts: 4

Catalog Number

2 3 1 **CB0103**

Additional heights and pole diameters may be available. Contact factory for your specific needs.

1 Smooth Shaft Catalog No.	1 Fluted Shaft Catalog No.	Shaft Diameter	Finished Height	Wall Thickness
3S8.125	3F8.125	3"	8'	.125
3S9.125	3F9.125	3"	9'	.125
3S10.125	3F10.125	3"	10'	.125
3S11.125	-	3"	11'	.125
3S12.125	-	3"	12'	.125
-	-	-	-	-
3S10.188	3F10.188	3"	10'	.188
3S11.188	3F11.188	3"	11'	.188
3S12.188	3F12.188	3"	12'	.188
-	-	-	-	-
4S10.125	-	4"	10'	.125
4S11.125	-	4"	11'	.125
4S12.125	-	4"	12'	.125
4S13.125	-	4"	13'	.125
4S14.125	-	4"	14'	.125
-	-	-	•	-
-	4F10.188	4"	10'	.188
-	4F11.188	4"	11'	.188
4S12.188	4F12.188	4"	12'	.188
4S13.188	4F13.188	4"	13'	.188
4S14.188	4F14.188	4"	14'	.188
4S15.188	4F15.188	4"	15'	.188
4S16.188	4F16.188	4"	16'	.188

2	ACCESSORIE	S
GFI15 GFI20	(15 amp GFCI receptacle outlet) (20 amp GFCI receptacle outlet)	
GFI-WPU	(20 amp GFCI receptacle with weather proof in-use cover)	Ų.
BAA	(Cast Banner Arm A for 24" wide banner)	(1) ······
BAB	(Cast Banner Arm B for 30" wide banner)	4:00
BAC	(Cast Banner Arm C for 30" wide banner)	
LR1	(Cast Ladder Rest 1)	
LR3	(Cast Ladder Rest 3)	
LR4	(Cast Ladder Rest 4)	(D) (M) (M) (M) (M) (M) (M) (M) (M) (M) (M
LR5	(Cast Ladder Rest 5)	
SIGN A	(Cast Sign A; 30" x 9", 8 letters/numbers on or requires Banner Arm to hang)	
SIGN B	(Cast Sign B; 31" x 7", 12 letters/numbers o Banner Arm to hang)	•
SIGN C line, require	(Cast Sign C; 27" x 11", two rows of 8 letter s Banner Arm to hang)	s/numbers on each VOUR SIGN
SIGN D	(Cast Sign D; 11" x 6 1/2", 4 letters/number	L
SIGN E numbers on	(Cast Sign E; comes with pole clamp, 24 1/2 one line)	2" x 6", 9 letters/
FPH1	(Flag Pole Holder)	



Specifications CB0103

Project:		
Fixture Type:	Quantity:	
Customer:	, , <u>, , , , , , , , , , , , , , , , , </u>	
		Illuminating

NA 101 102 114	Raw Unfinished Black Forest Green	53 56	100	Copper Clay
102		56		
	Forest Green		109	Silver
114	i diest Gleen	61	106	Black Verde
	Bright Red	70	118	Painted Chrom
107	White	71	105	Painted Coppe
112	Bright Blue	72	108	Textured Black
123	Sunny Yellow	73	125	Matte Black
120	Aqua Green	76	121	Textured Architectural Bronze
NA	Galvanized	77	127	Textured White
111	Navy	78	124	Textured Silve
103	Architectural Bronze	10	130	Aspen Green
104	Patina Verde	11	131	Cantaloupe
133	Lilac	13	132	Putty
	123 120 NA 111 103	123 Sunny Yellow 120 Aqua Green NA Galvanized 111 Navy 103 Architectural Bronze 104 Patina Verde	123 Sunny Yellow 73 120 Aqua Green 76 NA Galvanized 77 111 Nay 78 103 Architectural Bronze 10 104 Patina Verde 11	123 Sunny Yellow 73 125 120 Aqua Green 76 121 NA Galvanized 77 127 111 Navy 78 124 103 Architectural Bronze 10 130 104 Patina Verde 11 131